

8949H

ImagePro 8949H Portable LCD Projector



The ImagePro 8949H is a bright (4000 lumens) and versatile portable LCD projector with network control, and is HDTV ready

8949H FEATURES

- 4000 lumen brightness
- WXGA resolution (1280 X 800) 16:10
- Network capability RJ-45 for control, maintenance and security
- Easy Lamp access on top and 2000 hour hybrid filter on side
- Horizontal & vertical lens shift
- Optional bayonet style lenses available
- HDTV ready, HDMI input
- Audio pass-through for sound system operation when project is "off"



Manual Horizontal and Vertical Lens Shift for Perfect Image Alignment

THE ALL NEW

DUKANE

Education. Presentation. Inspiration.

www.dukcorp.com



ConVA by Dukane delivers control of classroom audio visual assets in sync with our Student Response System. Experience tomorrow's classroom today with ConVA. Visit www.convasystems.com.


Call Dukane: 800-676-2485

ImagePro 8949H

Portable LCD projector

Back Panel

Connections



FEATURES

- WXGA (1024 x 768) resolution
- 4000 ANSI lumens of brightness
- New 16:10 format
- Network Capability, RJ-45, connection
- Whiteboard & Blackboard Modes
- Easy lamp access on top & 2000 hour filter access on side
- Monitor loophrough & remote mouse control
- Optional bayonet style lenses available
- Audio pass-through when projector is off
- Horizontal & vertical lens shift
- Kensington lock slot & security bar
- Five Year Warranty and One Year Peace of Mind Service

8949H Projection Table

Image Size 16:10		Throw Distance	
Diagonal	Width	Min.	Max.
Inches	Inches	Feet	Feet
30	25	3.0	3.7
60	51	6.2	7.5
80	63	8.3	10.0
100	85	10.4	12.6
120	102	12.5	15.1
150	127	15.7	18.9
200	170	21.0	25.3
300	254	31.6	37.9

Throw Ratio (distance to width) 1.5 1.8

DUKANE

Dukane Corporation
 Audio Visual Products Division
 2900 Dukane Drive
 St. Charles, Illinois 60174
 800-676-2485
 630-584-5156
 avsales@dukcorp.com
 www.dukcorp.com/av



toll-free
 fax
 e-mail

Specifications

Image Element	0.75" polysilicon TFT x3
Brightness	4000 ANSI lumens, 3200 (whisper mode)
Resolution	1280 x 800 pixels (H X V), WXGA
Contrast	1000:1 (using active iris)
Scanning Frequency	fh 15-106 kHz, fv 50-120 Hz
Lens	Manual zoom (F=1.7 to 2.1), 1.2X. Horizontal & vertical lens shift, manual
Lens Throw Ratio	1.5 -1.8 :1 throw distance to image width
Keystone Correction	Digital vertical & horizontal +/-40 & +/- 20 deg.
Aspect Ratio	16:10 native, 4:3 selectable
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+ and UXGA Compressed, MAC13", MAC16"
Video Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, HDTV 1080i, 720p, 576i, 480i/p
Image Control	Freeze function, electronic magnification and pan
Mouse Control	Using USB
Projection Modes	Front/rear/ceiling
Color Reproduction	24 bit (16.7 million)
Lamp	275W UHB
Lamp Life	2000 hours (3000 hours Whisper Mode)
Audio	16W, 4 speakers, WOW Sound
Throw Distance	35" to 436"
Screen Size, diagonal	30" to 300"
Inputs, Video	(1) Component, RCA x 3 (BNC Shared) (1) S-video, Min DIN 4-pin, (1) Composite video, RCA x 1 (2) Audio, Stereo, RCA x 2, (L/R)
Inputs, Computer	(1) RGB Signal: D-sub, 15 pin, (1) RGB, BNC x 5 (shared component) (1) HDMI (2) Audio, Stereo mini jack Stereo Jack, wired remote
Outputs Monitor	15 pin, D-sub
Outputs Audio	Audio, Stereo mini jack x 1
Outputs,Control	9 pin D-sub Connector, RS232 USB type B (remote mouse only)
Network, Ethernet	RJ-45 port / 100Base-T
Security	Kensington slot, Security bar
Fan Level	35dB, (28dB in whisper mode)
Operating Temperature	41 to 95 deg. F (5-35 deg C)
Power	AC 100-120V, AC220-240V 50/60 Hz, 460 watt
Size (WxHxD)	16.5" x 5.5" x 12.6"
Weight	15.8 lbs.
Carton Size	21" x 14" x 19"
Shipping Weight	25 lbs.
Accessories Included	Remote control, batteries (AA), power cord, RGB cable, operator/safety manual.
Safety	UL60950, C-UL, FCC Part15, Class B, CE, EN60950
Optional Accessories	Lamp 456-8949H, Ceiling mount, universal; RPA-U, Filter; MUO5661
Optional Lenses	FL601 Short fixed, throw Ratio 0.8 SL602 Short 1.7 zoom, throw ratio 1.2 to 2.0 LL603 Long 2.0 zoom, throw ratio 1.9 to 3.9 UL604 Long 1.8 zoom, throw ratio 3.9 to 7.4

Five (5) year limited warranty on parts and labor in North America, lamp excluded (for other locations, local warranties apply). Includes Dukane's FREE 1 year Peace-of-Mind Loaner Program.

